

S5-GC(25-50)K

Solis Three Phase Grid-Tied Inverters

Efficient

- Max. efficiency 98.8%
- String current up to 16A
- 3/4 MPPT design, supports multiple orientation system design
- Night time PID recovery function, increases overall system yield (optional)
- Wide voltage range and low startup voltage

Smart

- Supports export power control
- Intelligent string monitoring, smart I-V curve scan
- Supports RS485, WiFi, GPRS
- Scan to register on SolisCloud, supports remote upgrade and control

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Globally recognised branded componentry for longer life
- Intelligent redundant fan-cooling

Economic

- Supports GPRS/WiFi communication with less wiring and reduced installation costs
- > 150% DC/AC ratio
- Supports high power modules for lower installation costs

Models:

S5-GC25K / S5-GC30K
S5-GC33K / S5-GC36K
S5-GC40K / S5-GC40K-HV
S5-GC50K-HV



DATASHEET

S5-GC(25-50)K

Models	25K	30K	33K	36K	40K	40K-HV	50K-HV									
Input DC																
Recommended max. PV power	37.5 kW	45 kW	49.5 kW	54 kW	60 kW	60 kW	75 kW									
Max. input voltage				1100 V												
Rated voltage				600 V												
Start-up voltage				180 V												
MPPT voltage range				200-1000 V												
Max. input current	32 A / 32 A / 32 A			4*32 A												
Max. short circuit current	40 A / 40 A / 40 A			4*40 A												
MPPT number/Max. input strings number	3/6			4/8												
Output AC																
Rated output power	25 kW	30 kW	33 kW	36 kW	40 kW	40 kW	50 kW									
Max. apparent output power	27.5 kVA	33 kVA	36.3 kVA	39.6 kVA	44 kVA	44 kVA	55 kVA									
Max. output power	27.5 kW	33 kW	36.3 kW	39.6 kW	44 kW	44 kW	55 kW									
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V					3/PE, 480 V										
Rated grid frequency	50 Hz / 60 Hz															
Rated grid output current	38.0 A / 36.1 A	45.6 A / 43.3 A	50.1 A / 47.6 A	54.7 A / 52.0 A	60.8 A / 57.7 A	48.1 A	60.1 A									
Max. output current	41.8 A	50.2 A	55.1 A	60.2 A	66.9 A	53.0 A	66.2 A									
Power factor	>0.99 (0.8 leading - 0.8 lagging)															
THDi	<3%															
Efficiency																
Max. efficiency	98.5%		98.6%	98.7%		98.8%										
EU efficiency	98.1%		98.2%	98.3%		98.4%										
Protection																
DC reverse-polarity protection	Yes															
Short circuit protection	Yes															
Output over current protection	Yes															
Surge protection	DC Type II / AC Type II															
Grid monitoring	Yes															
Anti-islanding protection	Yes															
Temperature protection	Yes															
Strings monitoring	Yes															
I/V Curve scanning	Yes															
Integrated AFCI (DC arc-fault circuit protection)	Yes ⁽¹⁾															
Integrated PID recovery	Optional															
Integrated DC switch	Optional															
General Data																
Dimensions (W*H*D)	647*629*252 mm															
Weight	38.2 kg		42.1 kg													
Topology	Transformerless															
Self-consumption (night)	<1 W															
Operating ambient temperature range	-25 ~ +60°C															
Relative humidity	0-100%															
Ingress protection	IP66															
Cooling concept	Intelligent redundant fan-cooling															
Max. operation altitude	4000 m															
Grid connection standard	G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EIFS 2018.2, IEC 62116, IEC 61727, IEC60068, IEC 61683, EN 50530															
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4															
Features																
DC connection	MC4 connector															
AC connection	OT terminal															
Display	LCD															
Communication	RS485, Optional: Wi-Fi, GPRS															

(1) Activation required.