

S5-GR3P(3-20)K

Solis Three Phase Grid-Tied Inverters

Efficient

- Max. efficiency 98.7%
- String current up to 16A
- Wide voltage range and low startup voltage

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Automatic voltage stabilization technology in weak grid conditions

Smart

- Supports export power control
- Supports RS485, WiFi, GPRS
- Scan to register on SolisCloud, supports remote upgrade and control

Economic

- Compact design, simple installation and maintenance
- > 150% DC/AC ratio
- Supports high power modules for lower installation costs

Models:

S5-GR3P3K / S5-GR3P4K

S5-GR3P5K / S5-GR3P6K

S5-GR3P8K / S5-GR3P9K

S5-GR3P10K / S5-GR3P12K

S5-GR3P13K / S5-GR3P15K

S5-GR3P17K / S5-GR3P20K



360° View

DATASHEET

S5-GR3P(3-20)K

Models	3K	4K	5K	6K	8K	9K	10K	12K	13K	15K	17K	20K	
Input DC													
Recommended max. PV power	4.5 kW	6 kW	7.5 kW	9 kW	12 kW	13.5 kW	15 kW	18 kW	19.5 kW	22.5 kW	25.5 kW	30 kW	
Max. input voltage								1100 V					
Rated voltage								600 V					
Start-up voltage								180 V					
MPPT voltage range								160-1000 V					
Max. input current					16 A / 16 A					32 A / 32 A			
Max. short circuit current					20 A / 20 A					40 A / 40 A			
MPPT number/Max. input strings number					2/2					2/4			
Output AC													
Rated output power	3 kW	4 kW	5 kW	6 kW	8 kW	9 kW	10 kW	12 kW	13 kW	15 kW	17 kW	20 kW	
Max. apparent output power	3.3 kVA	4.4 kVA	5.5 kVA	6.6 kVA	8.8 kVA	9.9 kVA	11 kVA	13.2 kVA	14.3 kVA	16.5 kVA	18.7 kVA	22 kVA	
Max. output power	3.3 kW	4.4 kW	5.5 kW	6.6 kW	8.8 kW	9.9 kW	11 kW	13.2 kW	14.3 kW	16.5 kW	18.7 kW	22 kW	
Rated grid voltage							3/N/PE, 220 V / 380 V, 230 V / 400 V						
Grid voltage range							304-437 V / 320-460 V						
Rated grid frequency							50 Hz / 60 Hz						
Rated grid output current	4.6 A / 4.3 A	6.1 A / 5.8 A	7.6 A / 7.2 A	9.1 A / 8.7 A	12.2 A / 11.5 A	13.7 A / 13.0 A	15.2 A / 14.4 A	18.2 A / 17.3 A	19.8 A / 18.8 A	22.8 A / 21.7 A	25.8 A / 24.6 A	30.4 A / 28.9 A	
Max. output current	4.7 A	6.4 A	7.9 A	9.5 A	12.7 A	14.3 A	15.9 A	19.1 A	20.7 A	23.8 A	27 A	31.8 A	
Power factor							>0.99 (0.8 leading - 0.8 lagging)						
THDi							<2%						
Efficiency													
Max. efficiency			98.3%				98.5%			98.6%		98.7%	
EU efficiency			97.7%				97.9%			98.0%		98.1%	
Protection													
DC reverse-polarity protection								Yes					
Short circuit protection								Yes					
Output over current protection								Yes					
Surge protection								Yes					
Grid monitoring								Yes					
Anti-islanding protection								Yes					
Temperature protection								Yes					
Integrated AFCI (DC arc-fault circuit protection)								Yes ⁽¹⁾					
Integrated DC switch								Optional					
General Data													
Dimensions (W*H*D)							310*563*219 mm						
Weight					17.8 kg				18.8 kg		20 kg		
Topology							Transformerless						
Self-consumption (night)							<1 W						
Operating ambient temperature range							-25 ~ +60°C						
Relative humidity							0-100%						
Ingress protection							IP66						
Cooling concept					Natural convection				Intelligent redundant fan-cooling				
Max. operation altitude							4000 m						
Grid connection standard					G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530								
Safety/EMC standard						IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4							
Features													
DC connection							MC4 connector						
AC connection							Quick connection plug						
Display							LCD						
Communication							RS485, Optional: Wi-Fi, GPRS						

(1) Activation required.