

## S6-E01P(4-5)K-48

# Solis Single Phase Low Voltage Off-Grid Inverters

### Features:

- One-click fast charging mode
- 6 customisable charge/discharge time settings
- Supports 1ph and 3ph flexible connection with max 30kW in parallel
- Generator connectivity with multiple input methods and automatic generator On/Off control
- The newly added force-charging period can optimize the revenue according to the difference of electricity price
- Battery equalization for increased battery performance and lifespan

### Models:

S6-E01P4K-48 / S6-E01P5K-48



**DATASHEET**
**S6-E01P(4-5)K-48**

Models	4K	5K
<b>Solar Charger</b>		
Recommended max. PV power	5.5 kW	6.5 kW
Max. input voltage	500 V	
Start-up voltage	90 V	
MPPT voltage range	90-430 V	
Max. input current	32 A	
Max. short circuit current	40 A	
Max. solar charge current	100 A	
MPPT number/Max. input strings number	1/2	
<b>Battery</b>		
Battery type	Li-ion / Lead-acid	
Rated battery voltage	48 V	
Max. charge / discharge power	5 kW / 5 kW	
Max. charge / discharge current	100 A	
Communication	CAN/RS485	
<b>Inverter Output</b>		
Rated output power	4 kVA / 4 kW	5 kVA / 5 kW
Operation phase	1/N/PE	
Rated grid voltage	230 V ± 1%	
Rated grid frequency	50 Hz / 60 Hz ± 0.1%	
Surge capacity	8 kVA	10 kVA
Max. output current	20 A	25 A
Output voltage waveform	Pure sine wave	
Transfer time	10 ms typical, 20 ms Max	
THDv (@linear load)	<3%	
Peak efficiency (PV-AC)	96.6%	
<b>AC Charger</b>		
Rated input voltage	230 V	
Selectable voltage range	90-280 V	
AC frequency range	50 Hz / 60 Hz (Auto sensing)	
Max. AC charge current	60 A	80 A
<b>Generator</b>		
Rated input power	4 kW	5 kW
Rated input current	60 A	80 A
<b>Protection</b>		
Output over voltage protection	Yes	
Output over current protection	Yes	
Short circuit protection	Yes	
Surge protection	Yes	
Temperature protection	Yes	
Integrated AFCI (DC arc-fault circuit protection)	Yes	
<b>General Data</b>		
Dimensions (W*H*D)	335*450*160 mm	
Weight	14 kg	
Topology	High frequency non-isolation	
Relative humidity	5% - 95% (Non-condensing)	
Operating ambient temperature range	-10 ~ +60°C	
Storage temperature range	-25 ~ +60°C	
Ingress protection	IP21	
Max. operation altitude	2000 m	
Parallel capability	6 units	
Safety standard	IEC 62109, IEC 61000, 55011	
<b>Features</b>		
DC connection	Terminal connectors	
AC connection	Terminal connectors	
Display	LCD	
Communication	CAN, BMS, RS485, Dry-contact, Bluetooth, Optional: Wi-Fi	