

60-75K

SOLARATOR SERIES

Operates Seamlessly with Generator: Experience Uninterrupted Power, Even in Areas with Grid Instability

S6-EH3P(60-75)K10-LV-YD-H

Three Phase | High Voltage



12 Unique Advantages

- ★ Supports up to 2x rated PV input, maximizing solar energy utilization
- ★ Supports a maximum string input current of 21A, ensuring compatibility with high-power PV modules
- ★ Compatible with 100-314Ah battery modules, reducing overall system costs
- ★ Supports fast battery charging with a maximum charging current of 200A
- ★ Two independent battery ports for flexible configurations and easy capacity expansion
- ★ Delivers 200% overload for 200ms in off-grid mode, ensuring stable startup of heavy loads
- ★ Offers flexible control for weak grid and genset-hybrid scenarios, reducing investment costs
- ★ SolisCloud: Smart remote control, AI optimisation, and instant troubleshooting - all in one platform
- ★ Integrates PV and storage for demand management and anti-reverse flow functions
- ★ Provides dynamic reactive power compensation to improve grid power factor and reduce reactive power charges
- ★ Utility bypass function allows direct grid supply to backup loads
- ★ Patented cooling technology ensures reliable operation even under high-temperature conditions

6 Leading Advantages

- Supports both DC and AC coupling, for flexible retrofits and system expansions
- Ensures reliable backup power across diverse scenarios through battery reserve management
- Extends supply time for critical loads with intelligent load prioritization
- Offers a versatile three-in-one interface for seamless integration of on-grid PV, wind power, and diesel generators
- Achieves on- and off-grid transitions in less than 10ms, ensuring an uninterrupted power supply
- Supports multi-unit parallel operation up to 750kW (Solis STS cabinet recommended for systems over 6 units)

PHILIPPINES

t: +86 574 6580 2188 (sales) +63 2 8372 7945 (service)

e: sales@ginlong.com phservice@solisinverters.com

w: solisinverters.com



DATASHEET

Models	60K	75K
Input DC (PV side)		
Recommended max. PV array size	120 kW	150 kW
Max. usable PV input power	120 kW	150 kW
Max. input voltage		1000 V
Rated voltage		600 V
Start-up voltage		180 V
MPPT voltage range		150 - 950 V
Max. input current		10 × 42 A
Max. current per DC input		42 A
Max. short circuit current		10 × 60 A
MPPT number / Max. input strings number		10 / 20
Battery		
Battery type		Li-ion
Battery voltage range		300 - 950 V
Max. charge / discharge current		100 A × 2 / 100 A × 2
Number of battery port / Number of BMS port		2
Max. charge / discharge current of each port		100 A
Communication		CAN / RS485
Output AC (Grid side)		
Rated output power	60 kW	75 kW
Max. apparent output power	60 kVA	75 kVA
Rated grid voltage		3/(N)/PE, 127 V / 220 V, 133 V / 230 V
Rated grid frequency		50 Hz / 60 Hz
Rated grid output current	157.5 A / 150.6 A	196.8 A / 188.2 A
Power factor		> 0.99 (0.8 leading - 0.8 lagging)
THDi		< 3%
Input AC (Grid side)		
Max. input power		95.2 kW / 99.6 kW
Input voltage range		176 - 265 V
Max. input current		250 A
Output AC (Back-up)		
Rated output power	60 kW	75 kW
Max. apparent output power	1.6 times of rated power, 10 s; 2 times of rated power, 200 ms	1.4 times of rated power, 10 s; 1.6 times of rated power, 200 ms
Back-up switch time ^①		< 10 ms
Rated output voltage		3/(N)/PE, 127 V / 220 V, 133 V / 230 V
Rated frequency		50 Hz / 60 Hz
Rated output current	157.5 A / 150.6 A	196.8 A / 188.2 A
Max. AC passthrough current	157.5 A / 150.6 A	196.8 A / 188.2 A
THDv (@linear load)		< 3%
Input AC (Generator side)		
Max. input power	60 kW	75 kW
Rated input current	157.5 A / 150.6 A	196.8 A / 188.2 A
Rated input voltage		3/(N)/PE, 127 V / 220 V, 133 V / 230 V
Rated input frequency		50 Hz / 60 Hz
Efficiency		
Max. efficiency		96.0%
EU efficiency	94.5%	94.6%
BAT charged by PV / AC max. efficiency		97.6% / 95.6%
Battery discharged efficiency		95.6%
Protection		
Surge protection		DC Type II / AC Type II
Output over current protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Integrated PV switch		Yes
DC reverse-polarity protection		Yes
Protection class / Over voltage category		I / DC II, AC III
Integrated AFCI 2.0		Optional
Anti-islanding protection		Yes
General Data		
Max. power per phase (grid & back-up)		33% rated power
Dimensions (W × H × D)		1174 × 814 × 400 mm
Weight		170 kg
Inverter topology		Transformerless
Self-consumption		< 45 W
Operating temperature range		-25 ~ +60°C
Relative humidity		0 - 100%
Ingress protection		IP66
Cooling concept		Intelligent redundant fan-cooling
Max. operation altitude		3000 m
Grid connection standard ^②	G99, EN 50549-1&2/EN 50549-10, C10/11, IEC 62116, IEC 61727, PORTARIA N° 140, PORTARIA N° 515	
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4, EN 55011	
Features		
PV connection		MC4 connector
Battery connection		Terminal connector
AC connection		Terminal block
Display		7.0" LCD display & Bluetooth + APP
Communication interface	Standard: WIFI+LAN+Bluetooth, CAN-BMS×2, CAN-Parallel×2, LAN, RS485-Meter, RS485, DRM, DI×5, DO×4; Optional: 4G	

① From On-Grid Mode to Off-Grid Mode: For a single inverter system, switchover time <10ms.

For a parallel system which consists of up to 6 inverters, switchover time <20ms.
If customer wishes to connect more than 6 inverters in parallel, please contact Solis Technical Team.

② This column only shows the planned certification standards.

Please confirm the specific time of obtaining the standards with the local team.