

60-75K

SOLARATOR SERIES

Operates Seamlessly with Generator: Experience Uninterrupted Power, Even in Areas with Grid Instability

S6-EH3P(60-75)K10-LV-YD-H

Three Phase | High Voltage

12 Unique Advantages

- ★ Supports up to 2x rated PV input, maximizing solar energy utilization
- ★ Supports a maximum string input current of 21A, ensuring compatibility with high-power PV modules
- ★ Compatible with 100–314Ah battery modules, reducing overall system costs
- ★ Supports fast battery charging with a maximum charging current of 200A
- ★ Two independent battery ports for flexible configurations and easy capacity expansion
- ★ Delivers 200% overload for 200ms in off-grid mode, ensuring stable startup of heavy loads
- ★ Offers flexible control for weak grid and genset-hybrid scenarios, reducing investment costs
- ★ SolisCloud: Smart remote control, AI optimisation, and instant troubleshooting - all in one platform
- ★ Integrates PV and storage for demand management and anti-reverse flow functions
- ★ Provides dynamic reactive power compensation to improve grid power factor and reduce reactive power charges
- ★ Utility bypass function allows direct grid supply to backup loads
- ★ Patented cooling technology ensures reliable operation even under high-temperature conditions

6 Leading Advantages

- Supports both DC and AC coupling, for flexible retrofits and system expansions
- Ensures reliable backup power across diverse scenarios through battery reserve management
- Extends supply time for critical loads with intelligent load prioritization
- Offers a versatile three-in-one interface for seamless integration of on-grid PV, wind power, and diesel generators
- Achieves on- and off-grid transitions in less than 10ms, ensuring an uninterrupted power supply
- Supports multi-unit parallel operation up to 750kW (external ATS recommended for systems over 6 units)

PHILIPPINES

t: +86 574 6580 2188 (sales) +63 2 8372 7945 (service)
e: sales@ginlong.com phservice@solisinverters.com
w: solisinverters.com

DATASHEET

Models	60K	75K
Input DC (PV side)		
Recommended max. PV array size	120 kW	150 kW
Max. usable PV input power	120 kW	150 kW
Max. input voltage	1000 V	
Rated voltage	600 V	
Start-up voltage	180 V	
MPPT voltage range	150 - 950 V	
Max. input current	10 × 42 A	
Max. current per DC input	42 A	
Max. short circuit current	10 × 60 A	
MPPT number / Max. input strings number	10 / 20	
Battery		
Battery type	Li-ion	
Battery voltage range	300 - 950 V	
Max. charge / discharge current	100 A × 2 / 100 A × 2	
Number of battery port / Number of BMS port	2	
Max. charge / discharge current of each port	100 A	
Communication	CAN	
Output AC (Grid side)		
Rated output power	60 kW	75 kW
Max. apparent output power	60 kVA	75 KVA
Rated grid voltage	3/(N)/PE, 127 V / 220 V, 133 V / 230 V	
Rated grid frequency	50 Hz / 60 Hz	
Rated grid output current	157.5 A / 150.6 A	196.8 A / 188.2 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)	
THDi	< 3%	
Input AC (Grid side)		
Max. input power	95.2 kW / 99.6 kW	
Input voltage range	176 - 265 V	
Max. input current	250 A	
Output AC (Back-up)		
Rated output power	60 kW	75 kW
Max. apparent output power	1.6 times of rated power, 10 s; 2 times of rated power, 200 ms	1.4 times of rated power, 10 s; 1.6 times of rated power, 200 ms
Back-up switch time ①	< 10 ms	
Rated output voltage	3/(N)/PE, 127 V / 220 V, 133 V / 230 V	
Rated frequency	50 Hz / 60 Hz	
Rated output current	157.5 A / 150.6 A	196.8 A / 188.2 A
Max. AC passthrough current	157.5 A / 150.6 A	196.8 A / 188.2 A
THDv (@linear load)	< 3%	
Input AC (Generator side)		
Max. input power	60 kW	75 kW
Rated input current	157.5 A / 150.6 A	196.8 A / 188.2 A
Rated input voltage	3/(N)/PE, 127 V / 220 V, 133 V / 230 V	
Rated input frequency	50 Hz / 60 Hz	
Efficiency		
Max. efficiency	96.0%	
EU efficiency	94.5%	94.6%
BAT charged by PV / AC max. efficiency	97.6% / 95.6%	
Battery discharged efficiency	95.6%	
Protection		
Surge protection	DC Type II / AC Type II	
Output over current protection	Yes	
Insulation resistance monitoring	Yes	
Residual current detection	Yes	
Integrated PV switch	Yes	
DC reverse-polarity protection	Yes	
Protection class / Over voltage category	I / DC II, AC III	
Integrated AFCI 2.0	Optional	
Anti-islanding protection	Yes	
General Data		
Max. power per phase (grid & back-up)	33% rated power	
Dimensions (W × H × D)	1174 × 814 × 400 mm	
Weight	170 kg	
Inverter topology	Non-isolated	
Self-consumption	< 45 W	
Operating temperature range	-25 ~ +60°C	
Relative humidity	0 - 100%	
Ingress protection	IP66	
Cooling concept	Intelligent redundant fan-cooling	
Max. operation altitude	3000 m	
Grid connection standard ②	G99, EN 50549-1&2/EN 50549-10, C10/11, IEC 62116, IEC 61727, PORTARIA Nº 140, PORTARIA Nº 515	
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4, EN 55011	
Features		
PV connection	MC4 connector	
Battery connection	Terminal connector	
AC connection	Terminal block	
Display	7.0" LCD display & Bluetooth + APP	
Communication interface	Standard: WIFI+LAN+Bluetooth, CAN-BMS×2, CAN-Parallel×2, LAN, RS485-Meter, RS485, DRM, DI×5, DO×4; Optional: 4G	

① From On-Grid Mode to Off-Grid Mode: For a single inverter system, switchover time <10ms. For a parallel system which consists of up to 6 inverters, switchover time <20ms.If customer wishes to connect more than 6 inverters in parallel, please contact Solis Technical Team.

② This column only shows the planned certification standards. Please confirm the specific time of obtaining the standards with the local team.