

## S5-GR1P(7-10)K

# Solis Single Phase Grid-Tied Inverters

### Features:

- Max. efficiency 98.0%
- Wide voltage range and low startup voltage
- 3 MPPT design, suitable for multi-facing roof
- AFCI protection, proactively reduces fire risk
- 24-hour load consumption monitoring
- Adaptive weak grid

### Models:

S5-GR1P7K / S5-GR1P8K

S5-GR1P9K / S5-GR1P10K



## DATASHEET

Models	7K	8K	9K	10K
<b>Input DC</b>				
Recommended max. PV power	10.5 kW	12 kW	13.5 kW	15 kW
Max. input voltage	600 V			
Rated voltage	330 V			
Start-up voltage	120 V			
MPPT voltage range	100 - 500 V			
Max. input current	14 A / 14 A / 14 A			
Max. short circuit current	22 A / 22 A / 22 A			
MPPT number / Max. input strings number	3 / 3			
<b>Output AC</b>				
Rated output power	7 kW	8 kW	9 kW	10 kW
Max. apparent output power	7.7 kVA	8.8 kVA	9.9 kVA	10 kVA
Max. output power	7.7 kW	8.8 kW	9.9 kW	10 kW
Rated grid voltage	1/N/PE, 220 V / 230 V			
Rated grid frequency	50 Hz / 60 Hz			
Rated grid output current	31.8 A / 30.4 A	36.4 A / 34.8 A	40.9 A / 39.1 A	45.5 A / 43.5 A
Max. output current	33.7 A	36.6 A	41.3 A	45.9 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)			
THDi	< 3%			
<b>Efficiency</b>				
Max. efficiency	98.0%			
EU efficiency	97.1%			
<b>Protection</b>				
DC reverse-polarity protection	Yes			
Short circuit protection	Yes			
Output over current protection	Yes			
Surge protection	Yes			
Grid monitoring	Yes			
Anti-islanding protection	Yes			
Temperature protection	Yes			
Multi peak scan	Yes			
Integrated AFCI 2.0	Optional			
Integrated DC switch	Yes			
<b>General Data</b>				
Dimensions (W × H × D)	333 × 579 × 253 mm			
Weight	18.5 kg			
Topology	Transformerless			
Self-consumption (night)	< 1 W			
Operating ambient temperature range	-25 ~ +60°C			
Relative humidity	0 - 100%			
Ingress protection	IP66			
Noise emission (typical)	< 30 dB(A)			
Cooling concept	Natural cooling	Natural cooling with internal fan		
Max. operation altitude	4000 m			
Grid connection standard	G99, IEC 62116, IEC 61727, IEC 61683			
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4			
<b>Features</b>				
DC connection	MC4 connector			
AC connection	OT Terminal			
Display	LCD			
Communication	RS485, Optional: Wi-Fi, GPRS			