

S5-GC(25-40)K

Solis Three Phase Grid-Tied Inverters

Features:

- Max. efficiency 98.7%
- 3/4 MPPT design, suitable for multi-facing roof
- AFCI protection, proactively reduces fire risk
- Nighttime PID recovery function (optional)
- Intelligent string monitoring, smart I-V curve scan
- 24-hour load consumption monitoring
- IP66

Models:

S5-GC25K / S5-GC30K

S5-GC33K / S5-GC36K

S5-GC40K



360° View

DATASHEET

Models	25K	30K	33K	36K	40K
Input DC					
Recommended max. PV power	37.5 kW	45 kW	49.5 kW	54 kW	60 kW
Max. input voltage	1100 V				
Rated voltage	600 V				
Start-up voltage	180 V				
MPPT voltage range	200 - 1000 V				
Max. input current	32 A / 32 A / 32 A			4 × 32 A	
Max. short circuit current	40 A / 40 A / 40 A			4 × 40 A	
MPPT number / Max. input strings number	3 / 6			4 / 8	
Output AC					
Rated output power	25 kW	30 kW	33 kW	36 kW	40 kW
Max. apparent output power	27.5 kVA	33 kVA	36.3 kVA	39.6 kVA	44 kVA
Max. output power	27.5 kW	33 kW	36.3 kW	39.6 kW	44 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V				
Rated grid frequency	50 Hz				
Rated grid output current	38.0 A / 36.1 A	45.6 A / 43.3 A	50.1 A / 47.6 A	54.7 A / 52.0 A	60.8 A / 57.7 A
Max. output current	41.8 A	50.2 A	55.1 A	60.2 A	66.9 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)				
THDi	< 3%				
Efficiency					
Max. efficiency	98.5%		98.6%	98.7%	
EU efficiency	98.1%		98.2%	98.3%	
Protection					
DC reverse-polarity protection				Yes	
Short circuit protection				Yes	
Output over current protection				Yes	
Surge protection				DC Type II / AC Type II	
Grid monitoring				Yes	
Anti-islanding protection				Yes	
Temperature protection				Yes	
Strings monitoring				Yes	
I/V Curve scanning				Yes	
Multi peak scan				Yes	
Integrated AFCI 2.0				Optional	
Integrated PID recovery				Optional	
Integrated DC switch				Yes	
General Data					
Dimensions (W × H × D)	647 × 629 × 252 mm				
Weight	38.2 kg			42.1 kg	
Topology	Transformerless				
Self-consumption (night)	< 1 W				
Operating ambient temperature range	-25 ~ +60°C				
Relative humidity	0 - 100%				
Ingress protection	IP66				
Noise emission (typical)	≤ 60 dB(A)				
Cooling concept	Intelligent fan-cooling				
Max. operation altitude	4000 m				
Grid connection standard	G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1, VDE 0126/UTE C 15/VFR:2019, RD 1699/RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EIFS 2018.2, IEC 62116, IEC 61727, IEC60068, IEC 61683, EN 50530				
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4				
Features					
DC connection	MC4 connector				
AC connection	OT terminal				
Display	LCD				
Communication	RS485, Optional: Wi-Fi, GPRS				