

Compliance Document

No. D 086470 0071 Rev. 02

Holder of Certificate: **Ginlong Technologies Co., Ltd.**


No.57 Jintong Road
Binhai Industrial Park, Xiangshan
315712 Ningbo, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Product: **Converter**
Hybrid Inverter

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: www.tuvsud.com/ps-cert

Test report no.: 704092008109-02

Date, 2022-03-01



(Zhengdong Ma)



Compliance Document

No. D 086470 0071 Rev. 02

Model(s):

RHI-3K-48ES, RHI-3.6K-48ES, RHI-4.6K-48ES,
RHI-5K-48ES, RHI-3K-48ES-5G, RHI-3.6K-48ES-5G,
RHI-4.6K-48ES-5G, RHI-5K-48ES-5G, S5-EH1P3K-L,
S5-EH1P3.6K-L, S5-EH1P4.6K-L, S5-EH1P5K-L.

Parameters:

Please see page 3 to page 7

**Tested
according to:**

C10/11:2021

Compliance Document

No. D 086470 0071 Rev. 02

Model name	RHI-3K-48ES	RHI-3.6K-48ES	RHI-4.6K-48ES	RHI-5K-48ES
PV input parameters:				
Max. Input Voltage:	600 Vd.c.			
MPP Voltage Range:	90-520 Vd.c.			
Max. Input Current:	2×11 Ad.c.			
Isc PV:	2×17,2 Ad.c.			
Battery parameters:				
Battery Type:	Li-Ion			
Battery Voltage Range:	42-58 Vd.c.			
Max. Charge Current:	62,5 Ad.c.			
Max. Discharge Current:	62,5 Ad.c.			
AC-Output (Back-up) parameters:				
Rated Output Voltage:	230 Va.c.			
Rated Output Frequency:	50 Hz			
Rated Output Current:	13 Aa.c.			
Rated Output Power:	3000 W			
AC-Output (Grid Side) parameters:				
Rated Output Voltage:	230 Va.c.			
Rated Output Frequency:	50 Hz			
Rated Output Power:	3000 W	3600 W	4600 W	5000 W
Max. Apparent Output Power:	3300VA	4000VA	4600VA	5000VA
Max. Output Current:	15,7 Aa.c.	17,3 Aa.c.	23 Aa.c.	23,9 Aa.c.

Model name	RHI-3K-48ES	RHI-3.6K-48ES	RHI-4.6K-48ES	RHI-5K-48ES
Power Factor(adj.):	0,8(lagging)...0,8(leading)			
AC input parameters:				
Rated Voltage:	230 Va.c.			
Current (Maximum Continuous):	23,9 Aa.c.			
Rated Frequency:	50 Hz			
Others:				
Operating Temperature Range:	-25 °C...+60 °C			
Protective Class:	I			
Ingress Protection:	IP65			
Overvoltage Category:	II(PV), III(MAINS)			
Inverter Topology:	Non-isolated			

Compliance Document

No. D 086470 0071 Rev. 02

Model name	RHI-3K-48ES-5G	RHI-3.6K-48ES-5G	RHI-4.6K-48ES-5G
PV input parameters:			
Max. Input Voltage:	600 Vd.c.		
MPP Voltage Range:	90-520 Vd.c.		
Max. Input Current:	2×11 Ad.c.		
Isc PV:	2×17,2 Ad.c.		
Battery parameters:			
Battery Type:	Li-ion / Lead-acid		
Battery Voltage Range:	42-58 Vd.c.		
Max. Charge Current:	62,5 Ad.c.		100 Ad.c.
Max. Discharge Current:	62,5 Ad.c.		100 Ad.c.
AC-Output (Back-up) parameters:			
Rated Output Voltage:	230 Va.c.		
Rated Output Frequency:	50 Hz		
Rated Output Current:	13 Aa.c.		22 Aa.c.
Rated Output Power:	3000 W		5000 W
AC-Output (Grid Side) parameters:			
Rated Output Voltage:	230 Va.c.		
Rated Output Frequency:	50 Hz		

Model name	RHI-3K-48ES-5G	RHI-3.6K-48ES-5G	RHI-4.6K-48ES-5G
Rated Output Power:	3000 W	3600 W	4600 W
Max. Apparent Output Power:	3300VA	4000VA	4600VA
Max. Output Current:	15,7 Aa.c.	17,3 Aa.c.	23 Aa.c.
Power Factor(adj.):	0,8(lagging)...0,8(leading)		
AC input parameters:			
Rated Voltage:	230 Va.c.		
Current (Maximum Continuous):	26,1 Aa.c.		
Rated Frequency:	50 Hz		
Others:			
Operating Temperature Range:	-25 °C...+60 °C		
Protective Class:	I		
Ingress Protection:	IP65		
Overvoltage Category:	II(PV), III(MAINS)		
Inverter Topology:	Non-isolated		

Compliance Document

No. D 086470 0071 Rev. 02

Model name	RHI-5K-48ES-5G
PV input parameters:	
Max. Input Voltage:	600 Vd.c.
MPP Voltage Range:	90-520 Vd.c.
Max. Input Current:	2×11 Ad.c.
Isc PV:	2×17,2 Ad.c.
Battery parameters:	
Battery Type:	Li-ion / Lead-acid
Battery Voltage Range:	42-58 Vd.c.
Max. Charge Current:	100 Ad.c.
Max. Discharge Current:	100 Ad.c.
AC-Output (Back-up) parameters:	
Rated Output Voltage:	230 Va.c.
Rated Output Frequency:	50 Hz
Rated Output Current:	22 Aa.c.
Rated Output Power:	5000 W
AC-Output (Grid Side) parameters:	
Rated Output Voltage:	230 Va.c.
Rated Output Frequency:	50 Hz

Model name	RHI-5K-48ES-5G
Rated Output Power:	5000 W
Max. Apparent Output Power:	5000VA
Max. Output Current:	23,9 Aa.c.
Power Factor(adj.):	0,8(lagging)...0,8(leading)
AC input parameters:	
Rated Voltage:	230 Va.c.
Current (Maximum Continuous):	26,1 Aa.c.
Rated Frequency:	50 Hz
Others:	
Operating Temperature Range:	-25 °C...+60 °C
Protective Class:	I
Ingress Protection:	IP65
Overvoltage Category:	II(PV), III(MAINS)
Inverter Topology:	Non-isolated

Compliance Document

No. D 086470 0071 Rev. 02

Model name	S5-EH1P3K-L	S5-EH1P3.6K-L	S5-EH1P4.6K-L
PV input parameters:			
Max. Input Voltage:	600 Vd.c.		
MPP Voltage Range:	90-520 Vd.c.		
Max. Input Current:	2×15 Ad.c.		
Isc PV:	2×22,5 Ad.c.		
Battery parameters:			
Battery Type:	Li-ion / Lead-acid		
Battery Voltage Range:	42-58 Vd.c.		
Max. Charge Current:	62,5 Ad.c.	100 Ad.c.	
Max. Discharge Current:	62,5 Ad.c.	100 Ad.c.	
AC-Output (Back-up) parameters:			
Rated Output Voltage:	230 Va.c.		
Rated Output Frequency:	50 Hz		
Rated Output Current:	13,5 Aa.c.	22 Aa.c.	
Rated Output Power:	3000 W	5000 W	
AC-Output (Grid Side) parameters:			
Rated Output Voltage:	230 Va.c.		
Rated Output Frequency:	50 Hz		

Model name	S5-EH1P3K-L	S5-EH1P3.6K-L	S5-EH1P4.6K-L
Rated Output Power:	3000 W	3600 W	4600 W
Max. Apparent Output Power:	3300VA	4000VA	4600VA
Max. Output Current:	15 Aa.c.	18,5 Aa.c.	21 Aa.c.
Power Factor(adj.):	0,8(lagging)...0,8(leading)		
AC input parameters:			
Rated Voltage:	230 Va.c.		
Current (Maximum Continuous):	20,5 Aa.c.	25 Aa.c.	31,5 Aa.c.
Rated Frequency:	50 Hz		
Others:			
Operating Temperature Range:	-25 °C...+60 °C		
Protective Class:	I		
Ingress Protection:	IP65		
Overvoltage Category:	II(PV), III(MAINS)		
Inverter Topology:	Non-isolated		

Compliance Document

No. D 086470 0071 Rev. 02

Model name	S5-EH1P5K-L
PV input parameters:	
Max. Input Voltage:	600 Vd.c.
MPP Voltage Range:	90-520 Vd.c.
Max. Input Current:	2×15 Ad.c.
Isc PV:	2×22,5 Ad.c.
Battery parameters:	
Battery Type:	Li-ion / Lead-acid
Battery Voltage Range:	42-58 Vd.c.
Max. Charge Current:	100 Ad.c.
Max. Discharge Current:	100 Ad.c.
AC-Output (Back-up) parameters:	
Rated Output Voltage:	230 Va.c.
Rated Output Frequency:	50 Hz
Rated Output Current:	22 Aa.c.
Rated Output Power:	5000 W
AC-Output (Grid Side) parameters:	
Rated Output Voltage:	230 Va.c.
Rated Output Frequency:	50 Hz

Model name	S5-EH1P5K-L
Rated Output Power:	5000 W
Max. Apparent Output Power:	5000VA
Max. Output Current:	25 Aa.c.
Power Factor(adj.):	0,8(lagging)...0,8(leading)
AC input parameters:	
Rated Voltage:	230 Va.c.
Current (Maximum Continuous):	34,5 Aa.c.
Rated Frequency:	50 Hz
Others:	
Operating Temperature Range:	-25 °C...+60 °C
Protective Class:	I
Ingress Protection:	IP65
Overvoltage Category:	II(PV), III(MAINS)
Inverter Topology:	Non-isolated