

Attestation of Conformity

No. N8A 086470 0094 Rev. 03

Holder of Attestation: Ginlong Technologies Co., Ltd.

No.57 Jintong Road

Binhai Industrial Park, Xiangshan 315712 Ningbo, Zhejiang PEOPLE'S REPUBLIC OF CHINA

Product: Converter

Off-grid inverter

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 704092008131-03

Date, 2024-02-02

(Zhengdong Ma)

N M



This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.





Attestation of Conformity

No. N8A 086470 0094 Rev. 03

Model(s): S5-E01P4K-48, S5-E01P4K-48-P, S5-E01P5K-48,

S5-EO1P5K-48-P, S6-EO1P4K-48, S6-EO1P5K-48

S6-E01P4K-48-EU, S6-E01P5K-48-EU

Parameters:

Model	S5-EO1P4K-48, S5-EO1P4K-48-P	S5-EO1P5K-48, S5-EO1P5K-48-P
PV Input		
Max. Input Voltage d.c.	d.c. 500 V	
MPPT Voltage range Voltage d.c.	d.c. 90 V 480 V	
Max. input Current d.c.	d.c. 13 A/13 A	
Isc PV (absolute max.) d.c.	d.c. 32 A	
Battery	u.o.	0271
Battery Voltage Range d.c.	d.c. 40V 60 V	
Max. Charge Current d.c.	d.c. 100 A	
Max. Discharge Current d.c.	d.c. 100 A	
AC-Output (stand-alone)		
Max. Output Power	4 kVA/4 kW	5 kVA/5 kW
Nominal Output Voltage a.c.	1/N/PE AC 230V	
Output Frequency a.c.	50/60 Hz	
Max. Output Current a.c.	a.c. 20 A	a.c. 25 A
AC-Input		
Nominal Input Voltage a.c.	1/N/PE AC 230 V	
Max. Input Continuous Current a.c.	a.c. 26 A	a.c. 30 A
Input Frequency a.c.	50/60 Hz	
Others		
Protective Class	Class I	
Ingress Protection	IP 21	
Overvoltage Category	III (AC), II(DC)	
Operation Temperature Range	-10 °C60 °C	

Page 2 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.





Attestation of Conformity

No. N8A 086470 0094 Rev. 03

Model	S6-EO1P4K-48 S6-EO1P4K-48-EU	S6-EO1P5K-48 S6-EO1P5K-48-EU	
PV Input			
Max. Input Voltage d.c.	d.c. 500 V		
MPPT Voltage range	d.c. 90V 430 V		
Voltage d.c.			
Max. input Current d.c.	d.c. 16 A/16 A		
Isc PV (absolute max.) d.c.	d.c. 40 A		
Battery			
Battery Voltage Range d.c.	d.c. 40V 60 V		
Max. Charge Current d.c.	d.c. 100 A		
Max. Discharge Current	d.c. 100 A		
d.c.			
AC-Output (stand-alone)			
Max. Output Power	4 kVA/4 kW	5 kVA/5 kW	
Nominal Output Voltage	1/N/PE AC 230 V		
a.c.			
Output Frequency a.c.	50/60 Hz		
Max. Output Current a.c.	a.c. 20 A	a.c. 25 A	
AC-Input(For grid port and Ge	_ · · · /		
Nominal Input Voltage a.c.	1/N/PE AC 230 V		
Max. Input Continuous Current a.c.	a.c. 26 A	a.c. 30 A	
Input Frequency a.c.	50/60 Hz		
Others			
Protective Class	Class I		
Ingress Protection	IP 21		
Over voltage Category	III (AC), II(DC)		
Operation Temperature Range	-10°C60°C		

Tested according to:

EN 62109-1:2010 EN 62109-2:2011



This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

