

S6-EH3P(30-50)K-H

Solis Three Phase High Voltage Energy Storage Inverters

Features:

- 4 MPPTs, 8 strings at 20A, and up to 96kW usable PV input
- 140A/70A+70A max charge/discharge on two independently controlled ports
- Supports 1.6 times rated output for 2 seconds on the backup port
- Supports parallel operation of up to 6 units for on and off-grid use
- Operates as a grid-tied inverter without batteries when on-grid
- Multi-input generator connectivity with automatic on/off control
- Supports peak shaving control in both "self-use" and "generator" mode

Models:

S6-EH3P30K-H

S6-EH3P40K-H

S6-EH3P50K-H



DATASHEET

S6-EH3P(30-50)K-H

Models	30K	40K	50K
Input DC (PV side)			
Recommended max PV array size	60 kW	80 kW	100 kW
Max. usable PV input power	60 kW	80 kW	96 kW
Max. input voltage		1000 V	
Rated voltage		600 V	
Start-up voltage		180 V	
MPPT voltage range		150-850 V	
Max. input current	3*40 A		4*40 A
Max. short circuit current	3*60 A		4*60 A
MPPT number/Max. input strings number	3/6		4/8
Battery			
Battery type		Li-ion	
Battery voltage range		150-800 V	
Max. charge / discharge power	33 kW	44 kW	55 kW
Max. charge / discharge current		70 A*2 ⁽¹⁾	
No. of battery inputs		2	
Max. charge / discharge power of each input	33 kW	40 kW	40 kW
Communication		CAN/RS485	
Output AC (Grid side)			
Rated output power	30 kW	40 kW	50 kW
Max. apparent output power	30 kVA	40 kVA	50 kVA
Rated grid voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated grid frequency		50 Hz / 60 Hz	
Rated grid output current	45.6 A / 43.3 A	60.8 A / 57.7 A	76 A / 72.2 A
Max. output current	45.6 A / 43.3 A	60.8 A / 57.7 A	76 A / 72.2 A
Power factor		>0.99 (0.8 leading - 0.8 lagging)	
THDi		< 3%	
Input AC (Grid side)			
Max. AC passthrough current	91.2 A / 86.6 A	121.6 A / 115.4 A	152 A / 144.4 A
Rated input voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated input frequency		50 Hz / 60 Hz	
Input Generator			
Max. input power	30 kW	40 kW	50 kW
Rated input current	45.6 A / 43.3 A	60.8 A / 57.7 A	76 A / 72.2 A
Rated input voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated input frequency		50 Hz / 60 Hz	
Output AC (Back-up)			
Rated output power	30 kW	40 kW	50 kW
Max. apparent output power		1.6 times of rated power, 2 s	
Back-up switch time		< 10 ms	
Rated output voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated frequency		50 Hz / 60 Hz	
Rated output current	45.6 A / 43.3 A	60.8 A / 57.7 A	76 A / 72.2 A
THDv (@linear load)		< 2%	
Efficiency			
Max. efficiency		97.8%	
EU efficiency		97.4%	
BAT charged by PV Max. efficiency		98.5%	
BAT charged/discharged to AC Max. efficiency		97.5%	
Protection			
Anti-islanding protection		Yes	
Output over current protection		Yes	
Short circuit protection		Yes	
Integrated DC switch		Optional	
DC reverse-polarity protection		Yes	
Surge protection		DC Type II / AC Type II	
Integrated AFCI (DC arc-fault circuit protection)		Yes ⁽²⁾	
General Data			
Dimensions (W*H*D)		530*880*290 mm	
Weight		73 kg	
Topology		Transformerless	
Self-consumption (night)		<25 W	
Operating ambient temperature range		-25 ~ +60°C	
Relative humidity		0-95%	
Ingress protection		IP66	
Cooling concept		Intelligent redundant fan-cooling	
Max. operation altitude		4000 m	
Grid connection standard	G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1/EN 50549-10, VDE 0126 / UTE C 15/VFR:2019, NTS 631/RD 1699/RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA		
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4		
Features			
PV connection	MC4 Quick connection plug		
Battery connection	Terminal connector		
AC connection	Terminal Block		
Display	LCD + Bluetooth + APP		
Communication	CAN, RS485, Ethernet, Optional: Wi-Fi, Cellular, LAN		

(1) Supporting parallel 140A input. (2) Activation required.